

Pumps

- Industrial Heavy-Duty Triplex Plunger Pump
- Oil Bath Crankcase • Stainless Valves
- Brass Manifold • Thermo Pump Protector

Electric Motors

- Heavy-Duty • 1750 RPM • TEFC • Full Frame
- 1.15 and 1.25 Service Factors
- Thermal Overload Protection
- Continuous Duty • High Efficiency
- Continuous Duty V-Belt Drive System with 11 Gauge Belt Guard or Flange & Coupling Drive

Electrical Control Panel

- Nema 4 • Water Tight • Easy Access
- Heavy-Duty On/Off Cam Switch or Optional Auto Stop/Start with Time Delay

Frame

- All Welded • Powder Coated
- 1-1/2" Bent Steel Roll Cage
- Lifting Bar • 1/4" Motor and Pump Mounting Plate
- Mounted on Large 8" Casters
- Capacity for Two 400' Hose Reels (Optional)
- Stationary Units also Available

Includes

- Liquid Filled Pressure Gauge
- Adjustable Pressure Regulator
- Gun and Wand Assembly with Quick Coupler System for Machines Under 5000 PSI
- 0°/15°/25°/40° Nozzles • 1 Soap Nozzle
- Downstream Chemical Injection System on Machines Up To 7.5 HP
- 50' of High Pressure Hose

Options

- VFD • PLC • Pressure Transducer • **Auto Stop/Start - Add (/A)**
- **Stainless Steel - Add (/SS)** • Order either flat base or portable frames

Ideal for use in processing plants, mills and factories for everyday reliable cleaning. Stationary frame options are available for facilities that require a piped in system for multiple location cleaning and/or multiple gun use.



IS3606E-3-208/A-FB
 with **Flat Base Frame Option - Add (-FB)**
 (15 & 20 HP) & Optional Auto Stop/Start



**SCAN FOR
VIDEO!**



IS505E-3-575
 with **Flat Base Frame with Shroud
 Option - Add (-FBWS)** (5/7.5/10 HP),
 Optional Leg Frame & Auto Stop/Start



IS505E-3-575
 with Optional Auto Stop/Start
**(This unit comes standard
 with a Wheel Kit)**



Intertek
 Up to 8000 PSI

MODEL	GPM	PSI	DRIVE	HP	VOLTAGE
IS204FE-1	4	2000	FLANGE/COUPLING	5	220V-1PH
IS204FE-3	4	2000	FLANGE/COUPLING	5	208/230/460/575 V-3PH
IS204E-1	4	2000	V-BELT	5	220V-1PH
IS204E-3	4	2000	V-BELT	5	208/230/460/575 V-3PH
IS304FE-1	4	3000	FLANGE/COUPLING	7.5	220V-1PH
IS304FE-3	4	3000	FLANGE/COUPLING	7.5	208/230/460/575 V-3PH
IS304E-1	4	3000	V-BELT	7.5	220V-1PH
IS304E-3	4	3000	V-BELT	7.5	208/230/460/575 V-3PH
IS255FE-3	5	2500	FLANGE/COUPLING	7.5	208/230/460/575 V-3PH
IS208E-3	8	2000	V-BELT	10	208/230/460/575 V-3PH
IS306E-1	5.5	3000	V-BELT	10	220V-1PH
IS306E-3	5.5	3000	V-BELT	10	208/230/460/575 V-3PH
IS404FE-1	4	4000	FLANGE/COUPLING	10	220V-1PH
IS404FE-3	4	4000	FLANGE/COUPLING	10	208/230/460/575 V-3PH
IS1212E-3	12	1200	V-BELT	10	208/230/460/575 V-3PH
IS3606E-3	6	3600	V-BELT	15	208/230/460/575 V-3PH
IS465E-3	6.5	4000	V-BELT	20	208/230/460/575 V-3PH
IS505E-3	5	5000	V-BELT	20	208/230/460/575 V-3PH
IS310E-3	10	3000	V-BELT	20	208/230/460/575 V-3PH
IS2512E-3	12	2500	V-BELT	20	208/230/460/575 V-3PH
IS3685E-3	8.5	3600	V-BELT	20	208/230/460/575 V-3PH
IS654E-3	4.3	6500	V-BELT	20	208/230/460/575 V-3PH
IS704E-3	4	7000	V-BELT	20	208/230/460/575 V-3PH
IS808E-3	8	8000	V-BELT	50	208/230/460/575 V-3PH
IS1156E-3	6	11,500	V-BELT	50	208/230/460/575 V-3PH
IS150045E-3	4.5	15,000	V-BELT	50	208/230/460/575 V-3PH